



# BrakeGrip

**High-friction, quick-drying resin to improve safety and reopen roads quickly**

## Key benefits

- Improved grip where high friction properties are essential
- Easily applied directly to a range of surfaces
- Resin and aggregate both available in range of colours
- Apply and reopen the road in as little as 30 minutes

## Applications

BrakeGrip is applied directly onto surfaces with simple, low-cost equipment. Making it the ideal solution for a range of projects, including:

- High traffic car and pedestrian zones
- Coloured road surfaces
- Braking zones
- Pedestrian crossings
- Dangerous bends or junctions requiring anti-skid

BrakeGrip is available in red, grey & black

RAL 3020

RAL 7043

RAL 9017

Coloured aggregate with a high PSV is also supplied to match the chosen resin colour.

**A solution from one of the industry's most trusted names**

**Founded in 1972, Kelly Bros International develops and manufactures high quality products that help reduce hazards and danger on the roads, and ultimately saves lives.**

We are one of the industry's foremost manufacturers and we are a trusted supplier to authorities and agencies worldwide. All our products are manufactured in our sustainable manufacturing plant.

**kelly-bros.com**

## Easy application

Mix the resin with a simple battery-operated drill and mixing paddle.

Quickly and easily apply BrakeGrip directly onto a clean, dry surface using a squeegee/or roller for even application. Aggregate can then be spread over the resin to create a high-friction, anti-skid surface.

## Increased traffic safety

BrakeGrip's high-friction properties make it the ideal solution for heavily trafficked surfaces, braking areas and other potentially low-grip surfaces such as dangerous bends.


## Rapid reopening


BrakeGrip's simple application process, quick drying properties and consistent quality ensures roads can be re-opened to traffic quickly, with minimum disruption.





Note: Any repairs to the surface should be completed before application.


## How to use


- 

1 Ensure the area is clean and dry
- 

2 Edges, drains and manhole covers must be masked off
- 

3 Thoroughly mix the desired amount of resin using a drill and a mixing paddle
- 

4 Apply directly to the surface with a squeegee/roller
- 

5 Generously scatter aggregate to ensure uniform appearance
- 

6 Remove excess aggregate when the resin has fully dried

### IRELAND

+353 (0) 49 8547173

info@kellybros.ie

Baillieborough Road,  
Virginia, Co. Cavan,  
A82 DY05 Ireland

### UNITED KINGDOM

+ 44 (0) 1 454 312675

info@kelly-bros.com

Great Western Business Park,  
1 Hawkesworth Road,  
Yate, Bristol BS37 5NW  
United Kingdom

### INTERNATIONAL ENQUIRIES

+353 (0) 49 8547173

info@kellybros.ie